


Solar module with EFG cells



ASE-100-GT-FT

Module type key:

G = Glass

T = Tedlar

F = framed

T = Thermoplastic cell embedding



Frame with added mounting groove and fastening clamp for quick and easy installation.

RWE SCHOTT Solar produces high-performance modules in energy output classes 50 Wp and higher. High-quality crystalline EFG and MAIN cells ensure maximum energy yield. These modules have been awarded top ratings in a number of independent studies and surveys. Every module type is designed – from frame to connection box – for cost-effective system integration.

- Narrow output tolerance
- Quick and easy installation
- System voltage up to 800 V
- Optimum TISO-LEEE results
- EFG-Technology

Narrow output tolerance: A very narrow module output selection permits serial connection with low connection losses.

Quick and easy installation: The anodized aluminum frame and the preinstalled cable with MC[®]-Connectors ensure quick and easy installation.

System voltage up to 800 V: The Safety Class II module is configured for system voltage of up to 800 V. It is suitable for grid-connected systems as well as 24-V applications.

Optimum TISO-LEEE results: In outdoor testing, the ASE-100-GT-FT was rated as the most stable and reliable module with respect to nominal output.

EFG-Technology: The patented EFG-Technology employed by RWE SCHOTT Solar provides for highly economical wafer-production and low raw-material consumption.

Electrical data

The electrical data apply to standard test conditions (STC):

Irradiance at the module level of 1.000 W/m² with spectrum AM 1.5 and a cell temperature of 25 °C.



Nominal power	P_{nom}	95 Wp	100 Wp	105 Wp
Voltage at maximum-power point	U_{mpp}	34.1 V	34.5 V	35.0 V
Current at maximum-power point	I_{mpp}	2.8 A	2.9 A	3.0 A
Open-circuit voltage	U_{oc}	42.3 V	42.5 V	42.6 V
Short-circuit current	I_{sc}	3.2 A	3.2 A	3.3 A

The rated power may only vary by $\pm 5\%$ and all other electrical parameters by $\pm 10\%$.

Dimensions and weights



Dimensions (tolerances ± 2 mm)	644 x 1.282 mm ²
Thickness with frame (tolerances ± 1 mm)	35 mm
Overall height incl. connection box (tolerances ± 1 mm)	52 mm
Weight	approx. 8.5 kg

Characteristic data



Solar cells per module	72
Type of solar cell	EFG solar cell (multi-crystalline, 10 x 10 cm ² , full-square)
Connection	Connection box with cage clamps up to 4 mm ² , three bypass diodes, 2.5 mm ² -Suhner-cable with MC [®] -Connectors, length of pole: 1 m each

Cell temperature coefficients



Power	$T_K (P_n)$	- 0.47 % / °C
Open-circuit voltage	$T_K (U_{oc})$	- 0.38 % / °C
Short-circuit current	$T_K (I_{sc})$	+ 0.10 % / °C

Limits




Max. system voltage	800 V _{DC}
Operating module temperature	-40... +90 °C
Storm resistance	Wind speed of 130 km/h \triangleq 800 Pa and safety factor of 3

The right is reserved to make technical modifications.


Qualifications



The ASE-100-GT-FT complies with the requirements of IEC 61215, Electrical Protection Class II and the EWG guideline 89/392 (CE).



Current/voltage characteristics with dependence on irradiance and module-temperature.



RWE SCHOTT Solar GmbH

Carl-Zeiss-Str. 4

63755 Alzenau

P +49(0)60 23 / 91-05

F +49(0)60 23 / 91-17 00

E sales@rweschottsolar.com

I www.rweschottsolar.com


RWE
SCHOTT Solar